

POP ACTION SAFETY RELIEF VALVES FOR TANK MOUNTING

TYPE 75 – SIZE 2" NPT

This safety relief has wide applications on all types of storage and transport tanks. Major portion of the valves is inside the tank. Therefore it requires very little head room above the tank. Possibility of tampering is eliminated.

DISCHARGE CAPACITIES

SET Pr. PSIG	Discharge Cap. CFM/AIR	VALVE TYPE	
		MOBILE	STORAGE
150	8500	A	AS
235	13500	B	BS
250	14200	C	CS
275	15500	D	DS
325	18500	E	ES
390	21900	F	FS

Valves can be set to customer requirement.



SAFETY RELIEF VALVES FOR GENERAL APPLICATION : SERIES NO : 200

These relief valves are used to protect any enclosed LPG system.

e.g. Length of pipe between two shut-off valves, cylinders or tanks. These valves are ideal to relieve hydrostatic pressure

These are pop action valves and keep the loss to the minimum. After releasing the pressure, the safety valve sits firmly on the seat and seals completely.

DISCHARGE CAPACITIES

VALVE TYPE WITH PROPER PREFIX	IN-LET CONNECTION	FLOW CAPACITY CFM/AIR AT SET PRESSURE 250 PSI
201	1/4" NPT	280
202	1/2" NPT	475
203	3/4" NPT	1500
204	1" NPT	2500
2050	1 1/2" NPT	6000



Valve can be set to other pressures on request.

Design and Dimensions are subject to change without notice.